

hours there is a comparative absence of these phenomena. So much is this the case that for the two years investigated I have not succeeded in finding a single example of a peak or hollow, suitable for this research, between the hours of 6 and 7 P.M., or between those of 9 and 10 P.M.

I forbear to make further remarks on this subject, but hope in a short time to extend the investigation up to the present date, and to bring the results before this Society.

VI. "On a new Astronomical Clock, and a Pendulum Governor for Uniform Motion." By Sir WILLIAM THOMSON, LL.D., F.R.S.  
Received June 10, 1869.

It seems strange that the dead-beat escapement should still hold its place in the astronomical clock, when its geometrical transformation, the cylinder escapement of the same inventor, Graham, only survives in Geneva watches of the cheaper class. For better portable time-keepers, it has been altered (through the rack-and-pinion movement) into the detached lever, which has proved much more accurate. If it is possible to make astronomical clocks go better than at present by merely giving them a better escapement, it is quite certain that one on the same principle as the detached lever, or as the ship-chronometer escapement, would improve their time-keeping.

But the inaccuracies hitherto tolerated in astronomical clocks may be due more to the faultiness of the mercury compensation pendulum, and of the mode in which it is hung, and of the instability of the supporting clock-case or framework, than to imperfection of the escapement and the greatness of the arc of vibration which it requires; therefore it would be wrong to expect confidently much improvement in the time-keeping merely from improvement of the escapement. I have therefore endeavoured to improve both the compensation for change of temperature in the pendulum, and the mode of its support, in a clock which I have recently made with an escapement on a new principle, in which the simplicity of the dead-beat escapement of Graham is retained, while its great defect, the stopping of the whole train of wheels by pressure of a tooth upon a surface moving with the pendulum, is remedied.

Imagine the escapement-wheel of a common dead-beat clock to be mounted on a collar fitting easily upon a shaft, instead of being rigidly attached to it. Let friction be properly applied between the shaft and the collar, so that the wheel shall be carried round by the shaft unless resisted by a force exceeding some small definite amount, and let a governor giving uniform motion be applied to the train of wheel-work connected with this shaft, and so adjusted that, when the escapement-wheel is unresisted, it will move faster by a small percentage than it ought to move when the clock is keeping time properly. Now let the escapement-wheel, thus mounted and carried round, act upon the escapement, just as it does in the ordinary clock. It will keep the pendulum vibrating, and will, just as in the ordinary

clock, be held back every time it touches the escapement during the interval required to set it right again from having gone too fast during the preceding interval of motion. But in the ordinary clock the interval of rest is considerable, generally greater than the interval of motion. In the new clock it is equal to a small fraction of the interval of motion:  $\frac{1}{300}$  in the clock as now working, but to be reduced probably to something much smaller yet. The simplest appliance to count the turns of this escapement-wheel (a worm, for instance, working upon a wheel with thirty teeth, carrying a hand round, which will correspond to the seconds' hand of the clock) completes the instrument; for minute and hour-hands are a superfluity in an astronomical clock.

In various trials which I have made since the year 1865, when this plan of escapement first occurred to me, I have used several different forms, all answering to the preceding description, although differing widely in their geometrical and mechanical characters. In all of them the escapement-wheel is reduced to a single tooth or arm, to diminish as much as possible the moment of inertia of the mass stopped by the pendulum. This arm revolves in the period of the pendulum (two seconds for a one second's pendulum), or some multiple of it. Thus the pendulum may execute one or more complete periods of vibration without being touched by the escapement.

I look forward to carrying the principle of the governed motion for the escapement-shaft much further than hitherto, and adjusting it to gain only about  $\frac{1}{100}$  per cent. on the pendulum; and then I shall probably arrange that each pallet of the escapement be touched only once a minute (and the counter may be dispensed with). The only other point of detail which I need mention at present is that the pallets have been, in all my trials, attached to the bottom of the pendulum, projecting below it, in order that satisfactory action with a very small arc of vibration (not more on each side than  $\frac{1}{100}$  of the radius, or 1 centimetre for the seconds' pendulum) may be secured.

My trials were rendered practically abortive from 1865 until a few months ago by the difficulty of obtaining a satisfactory governor for the uniform motion of the escapement-shaft; this difficulty is quite overcome in the pendulum governor, which I now proceed to describe.

Imagine a pendulum with single-tooth escapement mounted on a collar loose on the escapement-shaft just as described above—the shaft, however, being vertical in this case. A square-threaded screw is cut on the upper quarter of the length of the shaft, this being the part of it on which the collar works, and a pin fixed to the collar projects inwards to the furrow of the screw, so that, if the collar is turned relatively to the shaft, it will be carried along, as the nut of a screw, but with less friction than an ordinary nut. The main escapement-shaft just described is mounted vertically. The lower screw and long nut collar, three-quarters of the length of the escapement-shaft, are surrounded by a tube which, by wheel-work, is carried round about five per

cent. faster than the central shaft. This outer shaft, by means of friction produced by the pressure of proper springs, carries the nut collar round along with it, except when the escapement-tooth is stopped by either of the pallets attached to the pendulum. A stiff cross piece (like the head of a T), projecting each way from the top of the tubular shaft, carries, hanging down from it, the governing masses of a centrifugal friction governor. These masses are drawn towards the axis by springs, the inner ends of which are acted on by the nut collar, so that the higher or the lower the latter is in its range, the springs pull the masses inwards with less or more force. A fixed metal ring coaxial with the main shaft holds the governing masses in when their centrifugal forces exceed the forces of the springs, and resists the motion by forces of friction increasing approximately in simple proportion to the excess of the speed above that which just balances the forces of the springs. As long as the escapement-tooth is unresisted, the nut collar is carried round with the quicker motion of the outer tubular shaft, and so it *screws upwards*, diminishing the force of the springs. Once every semiperiod of the pendulum it is held back by either pallet, and the nut collar screws *down* as much as it rose during the preceding interval of freedom when the action is regular; and the central or main escapement-shaft turns in the same period as the tooth, being the period of the pendulum. If through increase or diminution of the driving-power, or diminution or increase of the coefficient of friction between the governing masses and the ring on which they press, the shaft tends to turn faster or slower, the nut collar works its way down or up the screw, until the governor is again regulated, and gives the same speed in the altered circumstances. It is easy to arrange that a large amount of regulating power shall be implied in a single turn of the nut collar relatively to the central shaft, and yet that the periodic application and removal of about  $\frac{1}{50}$  of this amount in the half period of the pendulum shall cause but a *very small* periodic variation in the speed. The latter important condition is secured by the great moment of inertia of the governing masses themselves round the main shaft. I hope, after a few months' trial, to be able to present a satisfactory report of the performance of the clock now completed according to the principles explained above. As many of the details of execution may become modified after practical trial, it is unnecessary that I should describe them minutely at present. Its general appearance, and the arrangement of its characteristic parts, may be understood from the photograph now laid before the Society.

VII. "On the Effect of Changes of Temperature on the Specific Inductive Capacity of Dielectrics." By Sir W. THOMSON, LL.D., F.R.S.

[The publication of the text of this paper is postponed.]